

LONGSHINE Technologie GmbH

15" P-CAP TOUCH MONITOR

Model: FM-150



Note: Information and specification are subject to change without prior notice

Basic Specification:

Model	FM-150 TFT-LED Touch Monitor
LCD Panel	15 " TFT-LED Panel
Resolution	1024 x RGB x 768
Display Active Area	304.1 × 228.1
Response Time	12ms typ.
Contrast Ratio	700:1 typ.
Brightness	250 cd/m ² typ.
View Angle(CR≥10)	Horizontal:140 ^o Vertical:125 ^o typ.
Input Interface	VGA * 1 Audio * 1 USB * 3 (For Touch/ MSR card reader/Dual display) AC-in connector * 1
Plug and Play	DDC1/2B for analog mode;DDC2B for digital mode.
Power Management	VESA DPMS
Power Consumption	40W Max. (Measured from AC inlet)
Power Saving Mode	Less than 1W (Same as above condition)
Turn Off Mode	Less than 0.5W (Same as above condition)
Environment	
Operating Temperature	0 to 40°C
Relative Humidity	10% to 90%
Power Supply	Off line switching type
Input	100-240VAC 50/60Hz
Other Stands	Desktop & Wall-mount(include VESA type)
MSR Card Reader	USB interface Track 123 (Optional)
Dual Display	VFD Type: 20 columns x 2 lines, each column 5x7 dots 7"~10" Dual Display (VESA HOLE 75x75)(Optional)
Touch Screen	True-Flat PCAP
Interface	USB

CONTACT

LONGSHINE Technologie GmbH

Headquarters:

An der Strusbek 9, 22926 Ahrensburg, Germany

No 945 Boai Street, Jubei City, Hsinchu, Taiwan 30265

TEL: +49 4102 49220 FAX: +49 4102 40109

www.longshine.de

All rights reserved, including intellectual property rights. Changes to technical data reserved.

Delivery subject to availability. All liability that the data and illustrations are complete, actual or correct is

excluded. Copyright © 1981-2017 LONGSHINE Technologie GmbH.