



LCS-K702

2-Port USB and PS/2 KVM Switch

2 Cables included



Model No.	LCS-K702	
Number Of Computers Controlled	2	
Selection Method	Push Button and Hot-Key (PS/2 and/or USB Keyboard)	
LEDs	Red for PC Selection Green for PC On-Line ready	
PC Connectors	Video	1 x HDB-15 male (PS/2 & USB signal combined)
Console Ports	Keyboard	1 x 6 pin mini-DIN female
	Mouse	1 x 6 pin mini-DIN female
	Video	1 x HDB - 15 female
	Keyboard	1 x USB - A type female
	Mouse	1 x USB - A type female
Auto-Scan Interval	From 5 to 250 Seconds	
DDC, DDC2 monitor	Yes (Max. Resolution: 2048x1536)@85Hz	
Hot Swappable	Yes	
Operating systems supported	Windows 98SE/ME/2000/XP/2003 Server, Linux Mac OS9/OSX and Sun Micro System	
Device driver	No Need	
Power	By PS/2 and/or USB or Power Adaptor (Optional)	
Cable Length	6 feet (1.80 Meter)	
Dimensions (L X W X H)	14 x 8.5 x 4.5 cm	
Unit Weight	440 g	
Housing material	Metal	
Operating Temperature	32~ 122°F (0~ 50°C)	
Humidity	0%~80%RH	